

Product Specification

MT-1232



Model No.	MT-1232
Digits	3 3/4 digits 3999 counts
Accuracy	0.5% best accuracy
DCV	400mV/4V/40V/400V $\pm(0.5\%+4d)$, 600V $\pm(1.0\%+4d)$
ACV	4V/40V/400V $\pm(0.8\%+6d)$, 600V $\pm(1.0\%+6d)$
DCA	400 μ A / 4000 μ A / 40mA/400mA $\pm(1.0\%+10d)$, 10A $\pm(1.2\%+10d)$
ACA	400 μ A/4000 μ A/40mA/400mA $\pm(1.5\%+10d)$, 10 A $\pm(2.5\%+15d)$
Resistance	400 Ω $\pm(0.8\%+5d)$, 4k/40k/400K/4M Ω $\pm(0.8\%+4d)$, 40M Ω $\pm(1.2\%+10d)$
Frequency	1/10/100/1K/10K/100K/1M/10MHz $\pm(0.5\%+10d)$
Capacitance	4nF $\pm(0.5\%+9d)$, 40nF/400nF/4 μ F/40 μ F $\pm(3.5\%+8d)$, 100 μ F $\pm(5.0\%+8d)$
Temperature	(-20 $^{\circ}$ C~1000 $^{\circ}$ C) < 400 $^{\circ}$ C $\pm(1.0\%+5d)$, (-20 $^{\circ}$ C~1000 $^{\circ}$ C) \geq 400 $^{\circ}$ C $\pm(1.5\%+15d)$
Fuse	10A/250V
Power source	1.5V AA x 2 (not included)

Size (HXWXD)mm	147 x 78 x 41 mm
Test leads model no.	MT-9907
Individual packing	Color Box